

# PIPE PURGE KIT



Phone: +358 400 600 942 Email: sales@amapipetools.fi



### **AMA® Pipe Purge Kit**

PRODUCT CODE 20 000

The AMA Pipe Purge Kit is an excellent aid to reduce inert gas use and purging time. This system uses triple silicon discs to form an airtight seal.

Gas plugs, sizes
DN20 (3/4") - DN150 (6")

Flange welding kit
DN40 (1 1/2") - DN150 (6")

- Towing balls
- Each silicone seal can be replaced separately
- Heat resistance 300 °C
- Made in Finland



NEW SET



## **AMA® Pipe Purge Kit Contents**





#### **Case contents:**

Front plug, heat resistance 300 °C DN20, DN25, DN32, DN40, DN50, DN65, DN80, DN100, DN125, DN150 (Towing ball included in sizes DN20–DN50)			
Rear plug, heat resistance 300 °C			
DN25, DN32, DN40, DN50, DN65, DN80, DN100, DN125, DN150			
Flange purge spindle			
Flange purge plate (heat resistance 250°C)	DN40 / DN50 / DN65 / DN80		
Flange purge plate (heat resistance 250°C)	DN100 / DN125 / DN150		
Intermediate rod, rigid	150 mm		
Intermediate rod, rigid	200 mm		
Intermediate rod, flexible	150 mm		
Intermediate rod, flexible	200 mm		
Flexible intermediate rod	250 mm		
Flexible intermediate rod M5 (incl. towing balls)	135 mm		
Gas hose	8 m		
Pulling wire	10 m		
Towing ball	DN65 / DN80		
Towing ball	DN100 / DN125 / DN150		
Accessory box for small parts			

#### **Approximate purging times\***

Plug size	Inner diam. Ø	Flow L/min.	Time min.
DN20	22–26	3	1
DN25	27-33	3	1
DN32	38-45	4	1
DN40	42-51	4	1
DN50	52-61	4	1,5
DN65	71–81	5	1,5
DN80	82-94	7	1,5
DN100	101–115	11	1,5
DN125	128-143	15	1,5
DN150	155–172	16	2,5

<sup>\*</sup>The user is responsible for the success of the purging process; the manufacturer accepts no responsibility for the success of the purging process.

